

# Metal Cladding Systems Pty Ltd.

COLORBOND® | Aurubis | elZinc® | GALVABOND® | UniCote® | Vestis | ZINCALUME® | VMZINC®  
Aluminium | Brass | Copper | Corten | Galvanised Steel | Stainless Steel | Steel | Titanium Zinc

EMAIL ORDERS: [ORDERS@METALCSYSTEMS.COM.AU](mailto:ORDERS@METALCSYSTEMS.COM.AU)









ORDER QUERIES: 0400 495 300

PICK UP: 13-19 MALCOLM ROAD, BRAESIDE, VIC, 3195

SYSTEMS  
ORDER FORM

[www.metalcsystems.com.au](http://www.metalcsystems.com.au)

Business name: \_\_\_\_\_ Date: \_\_\_\_ / \_\_\_\_ / \_\_\_\_  
Phone number: \_\_\_\_\_ Quote ID: \_\_\_\_\_  
Contact name: \_\_\_\_\_ Pages: \_\_\_\_\_ of \_\_\_\_\_  
Email: \_\_\_\_\_ Delivery ☐ Pick up ☐  
Delivery address: \_\_\_\_\_ Date required: \_\_\_\_\_

Material		Colour:			
	25mm <input type="checkbox"/> 38mm <input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>
STANDING SEAM		INTERLOCKING/V25		BATTEN SEAM	
	25mm <input type="checkbox"/> 38mm <input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>
SNAPLOCK		FLATLOCK		SHINGLE	
	25mm <input type="checkbox"/> 38mm <input type="checkbox"/>		<input type="checkbox"/>	Tick the cladding system you require	
NAILSTRIP		RECESSED FLATLOCK			

PANEL LABEL	PAN (mm)	EXPRESS (mm)	COVER (mm)	QTY.	LENGTH (mm)	HOOKS/ STOP ENDS		LAY DIRECTION L - R / R - L	OFFICE USE ONLY
						TOP	BOTTOM		LENGTH (mm)
eg) A	295	10	305	4	2450	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	L - R	
1)									
2)									
3)									
4)									
5)									
6)									
7)									
8)									
9)									
10)									

NOTES (e.g: number of clips, custom corners, single starter panels, double overlaps, double underlaps, raked panels, foam infill etc.):

**Notes** - In this section draw any corner panel details, custom panels, tapered panels, stop end/hook lengths, foam infill and/or fixing clip quantity.

**Foam Backing** - Is only applicable when ordering Interlocking panels.

Metal Cladding System supply foam cut to width for Interlocking panels.

However, foam is not a standard product and is combustible. Metal Cladding Systems do not recommend foam on any commercial or multi-residential builds.

DIMENSION CLEARLY. Unreadable drawings will not be accepted. Re-submission of unclear orders and will not be responsible. Angles not otherwise stated, will be made at 90°. Tolerances apply to all products.

**Panel Label** - this is where you can create a reference to help identify panels on site.

eg: Wall A  
If panel labels are noted on this form, Metal Cladding Systems will label and pack each panel type together.

**Pan** - This is only applicable when ordering Interlocking panels.

Pan is the face width of the Interlocking panel.

Cover - express = pan

eg:  
305 mm cover - 10 mm express  
= 295 mm pan

**Express** - This is only applicable when ordering Interlocking panels. Express is the width of the recessed space between each panel.

The Interlocking express can be 0 mm - 25 mm. 0mm will be 2 - 3mm after manufacturing.

**Cover** - this is the total coverage of the panel on the wall and a key dimension for all panel systems.

Nailstrip, Snaplock and Standing Seam will all only have a cover measurement, centre of rib to centre (no pan or express needed).

Interlocking will have an express, pan and cover.

**Hooks/Stop ends** - Stop ends is a term usually applicable when ordering Interlocking. Hooks is a term usually applicable when ordering any other panel. However the terms are somewhat interchangeable.

A stop end is usually 25mm or custom. A hook is usually 20mm or custom.

When opting for only one end (eg. top) we will require the Lay Direction - Left to Right or Right to Left.

**Length** - Nominate the length you would like your panel made to. Panels can be made to almost any length. Standard lengths are 600 mm - 9000 mm.

(Panels 600 mm long or less, may incur an additional cutting down charge).